



Amarr

®



Model 3500 with Model 2400 top and bottom sections

Amarr's Model 3500 aluminum door is constructed of 2" thick extruded aluminum rails and stiles and can be fitted with solid aluminum panels or full-view glass. Perfect for service stations or fire stations, our aluminum door creates a clean look for any facility.

For doors over 12' 2" wide x 12' tall, an open back commercial steel ribbed bottom and top section is required with solid aluminum or full view glass intermediate sections.



WARRANTIES

- 1-year Limited Warranty on materials and workmanship
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details

Amarr is a registered trademark of The Amarr Company, North Carolina, U.S.A.

Construction

Model 3500

Extruded Aluminum Door



EXTRUDED ALUMINUM Aluminum or Full View Glass Panels

Track: All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

WINDOW OPTIONS



GLASS PANELS

COLORS

Actual color may vary from sample shown.



ANODIZED ALUMINUM



165 Carriage Court
Winston-Salem, NC 27105

800.503.DOOR
www.amarr.com

FOR PRODUCT BINDER:
1.800.503.3667

FOR TECHNICAL QUESTIONS:
1.877.512.6277

©2007 Amarr Garage Doors

Amarr reserves the right to change specifications and designs without notice and without incurring obligations.

Printed in USA Form #6220307/25M/HA
Amarr Garage Doors are the subject of one or more pending patents and/or U.S.A. or foreign patents.